


Rondelle tenuta / Washers


	Acciaio/gomma Steel/rubber (DOWTY)		Alluminio Aluminium		Rame Copper	
		kg		kg		kg
G 1/8	11600910021	0,0035	11600900055	0,0003	11600901068	0,0015
G 1/4	11600910049	0,0040	11600900158	0,0004	11600901111	0,0019
G 3/8	11600910085	0,0030	11600900309	0,0007	11600901166	0,0025
G 1/2	11600930125	0,0043	11600900452	0,0010	11600901200	0,0031
G 3/4	11600930349	0,0068	11600900596	0,0014	11600901255	0,0033
G 1	11600931008	0,0103	11600900658	0,0014	11600901308	0,0053
G 1- 1/4	11600931142	0,0127	11600900809	0,0022	11600901504	0,0067
G 1- 1/8			11600900756	0,0022		
G 1- 1/2	11600931124	0,0161	11600900854	0,0020	11600901559	0,0065
G 2	11600932007	0,0180				
G 2- 1/2	11600932123	0,0190				

Nippli doppi / Nipples


	G 1/4	G 3/8	G 1/2	G 3/4	G 1	G 1 1/4	G 1 1/2
G 1/8	11600600268						
G 1/4	11600600017	11600600026	11600600231				
G 3/8		11600600080	11600600099	11600600366			
G 1/2			11600600106		11600600240		
G 3/4			11600600160	11600600142	11600600151	11600600295	
G 1					11600600179	11600600204	11600600213
G 1- 1/4						11600600188	11600600222
G 1- 1/2							11600600197
G 2						11600600393	11600600400
G 2- 1/2						11600600419	11600600428

Nippli passaparete / Bulkhead fittings


Codice Code	C	A	B	L	CH
11601200064	G 3/8	31	12	54	22
11601200073	G 1/2	34	14	60,5	27
11601200082	G 3/4	37	16	66	32
11601200108	G 1	41	19	75	41
11601200117	G 1 1/4	45	20	81	50


Saracinesca / Gate valves


Codice Code		A	Peso Weight kg
12600300019	G 1/2	38	0,15
12600300028	G 3/4	44	0,26
12600300037	G 1	48	0,34
12600300046	G 1 - 1/4	51	0,56
12600300055	G 1 - 1/2	58	0,70
12600300064	G 2	63	1,16

Pressione esercizio max. / Max working pressure 16 bar

Valvole a sfera / Ball valves


Codice Code		A	Max. press. esercizio Max working press.	Peso Weight kg
12600500035	G 3/8	42	20 bar	0,12
12600500044	G 1/2	49	20 bar	0,16
12600500053	G 3/4	58	20 bar	0,25
12600500062	G 1	68	20 bar	0,43
12600500071	G 1 - 1/4	82	16 bar	0,60
12600500080	G 1 - 1/2	89	16 bar	0,93
12600500106	G 2	105	16 bar	1,35

Valvole a sfera orientabili / Orientable ball valves


Codice Code	A	B	C	Max. press. esercizio Max working press.	Peso Weight kg
12600600356	G 1 - 1/4	89	133,5	16 bar	0,7
12600600409	G 1 - 1/2	102	145,5	16 bar	1,22
12600600507	G 2	137	150	16 bar	1,8

Valvole a sfera / Ball valves F/F


Codice Code		A	Max. press. esercizio Max working press.	Peso Weight kg
12600700108	G 3/8	50	40 bar	0,12

Valvole a sfera / Ball valves M/F


Codice Code		A	Max. press. esercizio Max working press.	Peso Weight kg
12600700104	G 3/8	39	40 bar	0,12