

PISTON PUMPS "TWIN-FLOW" SERIES

We have the pleasure to inform you that the range of TWIN-FLOW piston pump is also available in the versions 70+70 cc.



The order codes are the following:

- **TWIN-FLOW 70+70:** **108-030-00685** right rotation
108-030-00694 left rotation

Unidirectional bent-axis piston pumps having two independent pressure lines.

The range includes also the following versions:

- **TWIN-FLOW 53+53:** **108-030-00505** right rotation
108-030-00514 left rotation
- **TWIN-FLOW 70+35:** **108-030-00701** right rotation
108-030-00710 left rotation

TECHNICAL WORKING FEATURES	53+53	70+70	70+35
Displacement A (cc/rev)	53	67.7	36.5
Displacement B (cc/rev)	55	66.2	68.3
Max continuous pressure (bar)	350	300	350
Max peak pressure (bar)	400	350	400
Max speed without load (rpm)	2550	2550	2550
Max speed with load on A and B outputs	1800	1650	1800
Max speed with load on 1 output only	2100	2100	2100
Max continuous power (kW)	111	108	108
Max intermittent power (kW)	127	123	123

ACCESSORIES FOR PISTON PUMPS "TWIN-FLOW" SERIES

- **BY-PASS VALVE FOR:**
TWIN-FLOW 53+53/70+35 12V: 108-200-12532
TWIN-FLOW 53+53/70+35 24V: 108-200-24538
TWIN-FLOW 70+70 12V: 108-200-12701
TWIN-FLOW 70+70 24V: 108-200-24707



For further information, please contact our Export Department.