




MULTI-FUNCTION HYDRAULIC DIVERTER "MODUL-GATE" WITH RELIEF VALVE

We have the pleasure to inform you that our MODUL-GATE diverters range now includes also the versions with relief valve positioned on the auxiliary diverter outputs.



121-016-10101



121-016-10209

Order codes are:

121-016-10101: Main valve + 1 double acting section + relief valve
121-016-10209: Main valve + 2 double acting sections + relief valve

TECHNICAL FEATURES OF MAIN VALVE			
Flow rate	I/min.	250	
Max. working pressure	bar	320	
Working temperature		-25 +80°C	
Oil viscosity		12 - 100 cSt	
Oil filtering		< 25 μm	
Standard pressure setting	bar	160	
Max. pressure setting	bar	280	
Max. pneumatic pressure	bar	12	

TECHNICAL FEATURES OF AUXILIARY VALVES			
Flow rate	l/min.	60	
Max. working pressure	bar	320	
Working temperature		-25° +80°C	
Oil viscosity		12 - 100 cSt	
Oil filtering		< 25 μm	
Max. pneumatic pressure	bar	12	
Pressure setting range	bar	131-320	
Tarage standard de pression	bar	150	

Rif: NEW-11-008-ING MODUL-GATE+VM

Mercoledì 28 settembre 2011